

Agrosurf GF

Specification	Appearance at 25°C	:	Clear amber liquid free from foreign matter
	Acid Value mg.KOG/g	:	0.7 Max
	Iodine Value cg.12/g	:	3.5 Max
	Oxirane Oxygen %	:	6.4 Min

Typical Properties	Composition	:	Epoxidised Soyabean Oil
	EPA Status	:	910, 930
	Solids Content %	:	100
	Odour	:	Alcoholic
	Viscosity at 25°C (cP)	:	348
	Specific Gravity at 25°C	:	0.995
	Solubility in Water	:	Insoluble
	Pour Point °C	:	-13
	Flash Point Closed Cup (°C)	:	>150

Typical properties are based on our own measurements and do not constitute part of the sales specification

Application Agrosurf GF is an epoxidised vegetable oil for use as a stabiliser in the formulation of a wide range of toxicant solvent systems but is particularly effective in situations where sensitivity to moisture or liberated acid accumulation is a problem.

Typically Agrosurf GF is used at concentration levels of between 0.5 - 2.0% to protect toxicant formulations from chemical instability.

Packaging Agrosurf GF can be supplied in bulk road tankers, IBC's or 200kg nett drums.

Storage Stainless steel, polyethylene or glass lined equipment is necessary for the storage of Agrosurf GF in order to prevent corrosion and subsequent contamination. This material can separate on standing and at low temperatures. May require agitation and warming prior to use.

All information, recommendations and suggestions appearing in the literature concerning the use of the product are based upon tests and data believed to be reliable. However it is the users responsibility to determine the suitability for their own use of the products described here. For non English datasheets translation has been carried out using translation software, Lankem accepts no liability due to errors that occur during translation.

Lankem Ltd
 Charles Street
 Dukinfield
 Cheshire
 SK16 4SD
 United Kingdom

Tel : 44 (0)161 343 3355
 Fax : 44 (0)161 343 3366

technical@lankem.co.uk
 www.lankem.eu

