

TECHNICAL DATA SHEET

Lanspec OF65

Specification Appearance at 25°C : Pale Yellow Liquid

SAM % (Equivalent Weight 374) : 64.0 - 66.0 pH (5% Aqueous) : 6.0 - 7.5

Typical Properties Composition : Alkyl ether sulfate ammonium salt

Activity % : 5

Odour : Characteristic

 Viscosity at 20°C (centipoise)
 :
 90

 pH (10% aqueous)
 :
 7.0-8.5

 Specific Gravity at 20°C
 :
 1.03

 Solubility in Water at 20°C
 :
 Soluble

 Pour Point °C
 :
 <-15°C</td>

 Flash Point °C - Closed Cup
 :
 28

Typical properties are based on our own measurements and do not constitute part of the sales specification

Application

Lanspec OF65 is an ammonium neutralised alkyl ether sulphate and finds application where high foaming, characteristics are required, particularly in the presence of highly levels of electrolyte and polyvalent metal ions. Lanspec OF65 has good stability in the presence of alkaline solutions at moderate temperatures, but will hydrolyse in acidic solutions. Lanspec OF65 finds applications in a range industries due to it's key properties which include:

Properties:

- High foaming surfactant
- Effective foaming agent for electrolyte solutions e.g. brine, seawater
- High foaming in the presence of polyvalent ions e.g. Calcium Magnesium
- Good foam stability in the presence of hydrocarbons
- Easily dilutable in cold water

Uses:

- General purpose foaming agent
- Oilfield foam drilling
- Gas well deliquification

Packaging

Lanspec OF65 can be supplied in bulk road tankers, IBC's, 200kg or 25kg nett drums.

Storage

Stainless steel, polyethylene or glass lined equipment is necessary for the storage of Lanspec OF65 in order to prevent corrosion and subsequent contamination. This material can separate on standing and at low temperatures. May require agitation and warming prior to use.

All information, recommendations and suggestions appearing in the literature concerning the use of the product are based upon tests and data believed to be reliable. However it is the users responsibility to determine the suitability for their own use of the products described here. For non English datasheets translation has been carried out using translation software, Lankem accepts no liability due to errors that occur during translation.

Lankem Ltd Charles Street Dukinfield Cheshire SK16 4SD United Kingdom

Tel: 44 (0)161 343 3355 Fax: 44 (0)161 343 3366 technical@lankem.co.uk www.lankem.eu





