

LANSPEC OF65

Page: 1

Compilation date: 20/06/2016

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LANSPEC OF65

Product code: LK-OF65

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SURFACTANT

**1.3. Details of the supplier of the safety data sheet** 

Company name: Lankem Ltd

Charles Street

Dukinfield

Cheshire

SK16 4SD

United Kingdom

Tel: 01613433355

Fax: 01613433366

Email: technical@lankem.co.uk

### **1.4. Emergency telephone number**

Emergency tel: 07932007892

### Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315

Most important adverse effects: Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage.

### 2.2. Label elements

Label elements:

Hazard statements:H226: Flammable liquid and vapour.H315: Causes skin irritation.H318: Causes serious eye damage.Signal words:DangerHazard pictograms:GHS02: FlameGHS05: Corrosion



Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

### LANSPEC OF65

Page: 2

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

3.2. Mixtures

## Hazardous ingredients:

AMMONIUM ALKYL (C6-10) ETHER SULPHATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	68037-05-8	-	Eye Dam. 1: H318; Skin Irrit. 2: H315	50-70%

#### PROPAN-2-OL

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	10-30%	
			STOT SE 3: H336		

### Section 4: First aid measures

|--|

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# LANSPEC OF65

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

6.1. Personal	precautions.	protective equ	ipment and	emergency	procedures
01111 010011ai	productiono,	p. 0.00000 090			procoduroo

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling		
Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.		
	Do not handle in a confined space. Avoid the formation or spread of mists in the air.	
	Smoking is forbidden. Use non-sparking tools.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from		

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

# LANSPEC OF65

Page: 4

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

## Specific end use(s): Surfactant

Section 8: Exposure controls/personal protection

## 8.1. Control parameters

### Hazardous ingredients:

### PROPAN-2-OL

### Workplace exposure limits:

	•		•	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3	1250 mg/m3	-	-

**Respirable dust** 

# **DNEL/PNEC** Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
	equipment are not a source of ignition.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	Prevent from entering in public sewers or the immediate environment.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Pale yellow	
Odour:	Characteristic odour	
Evaporation rate:	No data available.	
Oxidising:	No data available.	
Solubility in water:	Soluble	
Viscosity:	No data available.	
Boiling point/range°C:	>82 Melting point/range°C:	<5
Flammability limits %: lower:	No data available. upper:	No data available.
Flash point°C:	28 Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available. Vapour pressure:	No data available.
Relative density:	1.03 pH:	Approx. 7
VOC g/l:	No data available.	

# LANSPEC OF65

Page: 5

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Alkalis.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

### Hazardous ingredients:

# PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

## Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

# Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

# LANSPEC OF65

Page: 6

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

## Section 12: Ecological information

12.1. Toxicity

**Ecotoxicity values:** 

Species	Test	Value	Units
ALGAE	EC50	65	mg/l

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Recovery operations:
 Not applicable.

 Disposal of packaging:
 Arrange for collection by specialised disposal company.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# Section 14: Transport information

14.1. UN number

UN number: UN1987

14.2. UN proper shipping name

Shipping name: ALCOHOLS, N.O.S.

(CONTAINS PROPAN-2-OL)

# LANSPEC OF65

Marine pollutant: No

### 14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

# Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H225: Highly flammable liquid and vapour.
	H226: Flammable liquid and vapour.
	H315: Causes skin irritation.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.