

TECHNICAL DATA SHEET

Lansurf SML

Specification Appearance at 25°C : Amber coloured viscous liquid free from foreign matter

Saponification Value mg.KOH/g : 156.0 - 170.0

Acid Value mg.KOH/g : 8.0 Max

Hydroxyl Value mg.KOH/g : 330.0 - 380.0

Typical Properties Composition : Sorbitan Mono Laurate

 CAS Number
 :
 1338-39-2

 Solids Content %
 :
 100

Odour : Characteristic

 HLB Value
 :
 8.0

 Viscosity at 25°C (cP)
 :
 5000

 Specific Gravity at 20°C
 :
 1.04

 Solubility in Water
 :
 Insoluble

 Pour Point °C
 :
 15

 Flash Point Closed Cup °C
 :
 >113

Typical properties are based on our own measurements and do not constitute part of the sales specification

Application

Lansurf SML can be used singularly or in combination with the ester ethoxylates such as Lansurf SML20. This product is hydrophobic and finds use as an emulsifier in many waxes and creams for household applications. Used in combination with the ethoxylates, Lansurf SML is used in textiles, leather treatment, silicone oils and agrochemicals. This product is also found to be readily biodegradable and would not expect to persist indefinitely in the environment.

Packaging Lansurf SML can be supplied in bulk road tankers, IBC's and 200kg nett drums.

Storage Stainless steel, polyethylene or glass lined equipment is necessary for the storage of Lansurf SML in order to prevent corrosion and subsequent contamination. This material can separate on standing and at low temperatures. May require agitation and warming prior to

use.

All information, recommendations and suggestions appearing in the literature concerning the use of the product are based upon tests and data believed to be reliable. However it is the users responsibility to determine the suitability for their own use of the products described here. For non English datasheets translation has been carried out using translation software, Lankem accepts no liability due to errors that occur during translation. Typical properties are based on our own measurements and do not constitute part of the sales specification.