


Lansurf CDE-G

| | | | |
|----------------------|----------------------------|---|---|
| Specification | Appearance at 25°C | : | Clear amber liquid free from foreign matter |
| | Diethanolamine Content % | : | 5.0 Max |
| | Esters as Methyl Laurate % | : | 5.0 Max |
| | Water Content % | : | 1 Max |
| | Soap as Sodium Laurate % | : | 2.0 Max |

| | | | |
|---------------------------|--------------------------|---|---|
| Typical Properties | Composition | : | Coconut Diethanolamide with free glycerol |
| | CAS Number | : | 68603-42-9 |
| | Solids Content % | : | 100 |
| | Odour | : | Characteristic |
| | Viscosity at 40°C (cP) | : | 1146 |
| | Specific Gravity at 20°C | : | 1.007 |
| | Solubility in Water | : | Soluble |
| | Pour Point °C | : | <0 |
| | Flash Point °C | : | >100.5 |

Foam Height Scale



Wetting Scale



Typical properties are based on our own measurements and do not constitute part of the sales specification

Application Lansurf CDE-G is a coconut diethanolamide produced via the reaction procedure that gives a product containing some free glycerol. This product has good foaming stability, soil suspension and thickening properties and can be used as a foam stabiliser, detergent, emulsifier and dispersing agent. Lansurf CDE-G is used as a foam stabiliser, either alone or in blends. Lansurf CDE-G is used in industrial degreasing, metal cleaning, as an anti-frosting agent in the printing of man-made fibres, and as an emulsifier for solvents and waxes.

Packaging Lansurf CDE-G can be supplied in bulk road tankers and IBC's

Storage Stainless steel, polyethylene or glass lined equipment is necessary for the storage of Lansurf CDE-G in order to prevent corrosion and subsequent contamination. This material can separate on standing and at low temperatures. May require agitation and warming prior to use.

All information, recommendations and suggestions appearing in the literature concerning the use of the product are based upon tests and data believed to be reliable. However it is the users responsibility to determine the suitability for their own use of the products described here. For non English datasheets translation has been carried out using translation software, Lankem accepts no liability due to errors that occur during translation.

Lankem Ltd
 Charles Street
 Dukinfield
 Cheshire
 SK16 4SD
 United Kingdom

Tel : 44 (0)161 343 3355
 Fax : 44 (0)161 343 3366

technical@lankem.co.uk
 www.lankem.eu

