



Kemsurf OS38

Specification	Appearance at 25°C	:	Clear amber liquid free from foreign matter
	SAM % (Equivalent Weight 320)	:	37.0 - 39.0
	pH (5% Aqueous)	:	6.0 - 8.0
	Colour Hazen (5% Aqueous)	:	80 Max

Typical Properties	Composition	:	Sodium C14-16 alpha olefin sulphonate
	CAS Number	:	68439-57-6
	Odour	:	Mild
	Viscosity at 25°C (cP)	:	51.9
	Specific Gravity at 20°C	:	1.07
	Solubility in Water	:	Soluble
	Pour Point °C	:	-3
	Flash Point Closed Cup °C	:	>150
	Surface Tension at 0.1% Aqueous (mN/m)	:	31.6
	CMC (mg/l)	:	301



Typical properties are based on our own measurements and do not constitute part of the sales specification

Application Kemsurf OS38 has good foaming and excellent detergency. Kemsurf OS38 can be used in many industrial and domestic applications where good detergency and wetting are required. Typical examples include textile auxiliaries and industrial cleaning. This product is also used in emulsion polymerisation for the following systems:

- Styrene / Butyl Acrylate
- Vinyl Acetate

Packaging Kemsurf OS38 can be supplied in bulk road tankers, IBC's, 200kg or 25kg nett drums.

Storage Stainless steel, polyethylene or glass lined equipment is necessary for the storage of Kemsurf OS38 in order to prevent corrosion and subsequent contamination. This material can separate on standing and at low temperatures. May require agitation and warming prior to use.

All information, recommendations and suggestions appearing in the literature concerning the use of the product are based upon tests and data believed to be reliable. However it is the users responsibility to determine the suitability for their own use of the products described here. For non English datasheets translation has been carried out using translation software, Lankem accepts no liability due to errors that occur during translation. Typical properties are based on our own measurements and do not constitute part of the sales specification.